



## MC 750-15W WHEEL CONVEYOR



**Irish Manufacturing Services Limited**

34a Dunroe Road, Clogher, Co. Tyrone,  
N. Ireland, BT76 0DZ

**T:** +44 (0)28 8554 9656

**E:** [info@ims-ltd.ie](mailto:info@ims-ltd.ie)

**Irish Manufacturing  
Services Ltd**

[www.ims-ltd.ie](http://www.ims-ltd.ie)



A leading manufacturer of screening and conveyor equipment, offer the MC750-15W wheeled stacking conveyor, the ideal solution for stockpiling materials from static or mobile screens

### **Heavy Duty Construction**

Constructed from MS plate designed in 12" (300mm) deep section to give added stability and use in heavy duty applications

### **Conveyor**

The conveyor is constructed in 2 sections , the tail section includes a generous feed hopper and the head section includes the conveyor drive , consisting of either a Sauer-Danfoss hydraulic motor or a Nord 7.5kw geared motor connected to a rubber lagged drive pulley

### **Undercarriage**

The undercarriage consists of an adjustable support trestle arrangement, mounted on a single axle with 2 No. 11.5/80-15.3 flotation wheels for added mobility. The wheels can be manually rotated through 90° to provide a radial function, increasing the stockpile capability of the conveyor

### **Head Folding**

The folding mechanism of the conveyor head section allows for quick site set up and provides a flexible approach to transport of the unit.

### **Tail Section**

The Tail Section consists of a generous 2m<sup>3</sup> capacity Reception Hopper, designed to accept material from a chute or a loading shovel. The tail section includes a self cleaning tail pulley and closely fitted trough rollers under the reception area. The tail section is complete with a ballast box and radial pivot

### **Emergency Stop System**

Every MC750-15W Conveyor is equipped from the factory with an emergency stop system that will render the plant inoperable when activated, providing added safety for the operator.

### **Standard Features**

Wheel Axle and Tow Bar

Choice of Hydraulic or Electric Drive

30" (750mm) wide 3 ply belt

Folding on Head Section

Manual Raise and Lower from 10 to 26°

## Options

Hydraulic Raise and Lower; Heavy Duty Belt;  
Chevron Belt;  
Impact Bars under Feed Point;  
Conveyor Belt Variable Speed Control  
PVC covers;  
Galvanised Steel Covers

## Specifications

Operational length	50' (15M")
Operational height	21'4" (6.5M")
Loading height	4'0" – 11' 3" (1.2M – 3.4M)
Transport width	7'4" (2.25 M")
Transport height	8'2" (2.5 M")
Transport length	40' 3" (12.2M")
Total weight	7600 lbs (3450 kgs)

*Due to Irish Manufacturing Services Limited's policy of continuing product improvements, specifications are subject to change without notice or obligation. No representation is made that the products depicted herein comply with any laws, codes, rules, regulations or standards. Compliance is the responsibility of the user. Additional safety equipment may be required by the particular location and application of product.*

**Irish Manufacturing Services Limited, 34a  
Dunroe Road, Clogher, Co. Tyrone, N. Ireland  
BT76 0Dz**



**Tel. +44 (0)28 8554 9656 E-mail [info@ims-ltd.ie](mailto:info@ims-ltd.ie) website; [www.ims-ltd.ie](http://www.ims-ltd.ie)**